



---

Name **15.6 inch High brightness, Splash proof true flat PCAP multi-touch monitor**

---

Spec. 1000 cd/m<sup>2</sup>  
Splash proof  
Projected Capacitive touch screen  
Matel enclosure chassis.  
Desktop Stand or openframe brackets optional.

---

## Product Introduction

---



## **15.6 inch High brightness, Splash proof true flat PCAP multi-touch monitor**

Made in Taiwan

No more dispute on the numbers and position of bright dots whether they are acceptable by standard requirement.

Adopt Projected Capacitive Multi-Touch panel from prestige vendors, USB interface controller, 99% accuracy in touch and durability reach more than 10 millions touch.

User may even wear a glove to interact the touch. We provide calibration software, and users may appropriately enjoy the touch experience.

Metal enclosure design provides rapid heat dissipation; durable and no swaying when touch the screen; SGS Bump, heat and humidity rigid test approved. CE & FCC Approved

Button on the back front avoids random setup, Stylish Design.

Multiple stand option, standard VESA wall bracket, or Exclusive openframe design set which is for ATM, ticket stand, Point of Information, Industrial Computer.

Multiple customized options i.e. High brightness panel (1,000 cd/m<sup>2</sup>), or add AR Anti-reflection /AG Anti-glare, Anti-Finger Print.

provides multiple touch options i.e. PCT, Resistive, IR, S.A.W., and sizes are complete.



### **Distinguishing Features:**

- The max resolution: 1366X768
- Component Video Connector: VGA(Dsub, 15pin), DVI-D
- Touch: Projected Capacitive Multi-Touch
- Splash proof / High Brightness 1000cd/m2 / sunlight readable.
- OS: support Win8, Win7, and all the OS before Win7, **Android**, Linux, DOS, MAC

### **Optional Specifications:**

- Desk stand/Wall mount bracket/ Exclusive openframe
- Protection: AR (Anti-reflection)/AG (Anti-glare), Anti-Finger Print.
- Touch interface: USB(Standard)

---

### Desktop Stand: B Stand(optional)

- ▲ Tilt 90 degree
- ▲ Special stand for touch
- ▲ Concise Routing design



---

### Desktop Stand: Z Stand(optional)

- ▲ Tilt 180 degree
- ▲ Monitor rotate 360 degree
- ▲ Special stand for touch; Similar to picture frame



---

### Openframe(optional)

- ▲ Left/right or Up/down, or Both
- ▲ Thickness: 1.8mm
- ▲ Multi set of hole long/Width, or oval. Easy to arrange.



---

### Standard VESA Wall mount Bracket(optional)

- ▲ Cross action adjust
- ▲ Compatible with all the VESA Wall Mount bracket.



## Display Characteristics

Model No.	P156	Resolution	1366x768 (HD)
Screen Diagonal	15.6 inch	Brightness	Optional
Color	16.7M Colors	Contrast Ratio	500:1
Display Area	344.2x193.5 mm	Viewing Angle (L/R)	160° (CR=5)
Display Ratio	16:9	Viewing Angle (U/D)	160° (CR=5)
Backlight Unit	LED	Response Time	10 msec
Operating Temp.	-20-60°C	Surface Treatment	AG coating

## General Specification

Speaker	2Wx2	Dimension	385.4x240x41 mm
Wall Mount Holes	75x75 & 100x100 mm	Net Weight	3.5 KG
Housing Material	Galvanized Steel	Gross Weight	4.5 KG
Display interface	VGA & DVI	Other connectors	Audio-in, DC-in

## Touch Specification

Type	Projected Capacitive	Model No.	P156B
Allowed touch points	10 point	Transparency	≥88%
Operating Temp.	-30~70°C	Haze	2%
Interface	USB (typ.) / RS-232 (opt.)	Hardness	≥7H

## Customized Options

Brightness	1000 cd/m2	Surface Splash Proof	Option
Surface Protection	Tempered glass	Color	Any Color (MOQ requested)
Coating Film	AG/AR/AF	Panel Mount Bezel	Customized Option
Open-frame bracket	Option		